



PRODUCT INFORMATION & DATA SHEET

ATF 6

This reduced-viscosity, multi-vehicle ATF features optimized thermal-viscosity properties and improved cold-flow performance, ensuring exceptional protection and compatibility with a wide range of vehicles across generations requiring DEXRON VI specified fluid. Engineered to exceed the demanding challenges of new transmissions, this ATF offers exceptional anti-shudder, anti-wear, and friction durability, along with superior oxidation stability, foam protection, and seal compatibility, surpassing the performance aspects of previous GM DEXRON ATF generations.

Performance level

GM DEXRON VI

Vital benefits

- ✓ Especially for 6-speed and newer gearboxes
- ✓ Compatible with all previous DEXRON versions
- ✓ Formulated for high-efficiency power transfer
- ✓ Reduces internal drag in modern transmissions
- ✓ Prevents clutch shudder and vibration issues
- ✓ Ensures smooth and consistent gear shifting
- ✓ Very stable viscosity under high shear stress
- ✓ Supports extended drain and service intervals

Areas of application

Developed for use in multi-speed automatic transmissions, power steering, and hydraulic systems of a wide range of passenger cars, SUVs and light-duty trucks requiring DEXRON VI specified ATF. Fully compatible with earlier DEXRON fluid specifications.

Typical properties

Fluid Colour		Red
Viscosity Index (VI)	ASTM D2270	154
Viscosity at 100 °C; mm ² /s	ASTM D445	6.0
Viscosity at 40 °C; mm ² /s	ASTM D445	29.8
Density at 15 °C; kg/m ³	ASTM D4052	847.0
Foam Test	ASTM D892	Pass
Flash Point; °C, open cup	ASTM D92	220
Pour Point; °C	ASTM D97	-45

Service recommendation

We advise draining and replacing the fluid according to the manufacturer's instructions. Be sure to refer to the owner's manual and monitor fluid levels during scheduled service interval. This ATF should not be used in any CVT and DCT transmissions unless recommended by the manufacturer.

Commercially available product compatibility

Compatible with any synthetic and conventional fluid of equivalent performance specifications. However, maximum performance is assured only when used on its own.

Disclosure

The product information and typical properties are subject to change without notice. We reserve the right to alter the technical data to align with ongoing technical developments.

Latest update of PIDS: 03/2025

Prince Global Pte Ltd
9 Raffles Pl, 22-01 Republic Plaza,
Singapore 048624.

info@princelubricants.com
www.princelubricants.com

